

## UNIVERSAL POLE ELECTROMAGNET CHUCK



### FEATURES

- Single solid piece body construction.
- 100% leak proof construction.
- Lowest height electro magnetic chucks.
- Low power consumption with little temperature rise.
- Possibility of combining several chucks for a large uninterrupted work surface.
- Low profile enables more grinding wheel head clearance.

### APPLICATIONS

- Ideal for standard components and for precision grinding.
- The low magnetic flux does not interfere with the grinding operation thereby giving higher accuracy.
- Designed to meet the demands of the latest grinding operations which require both heavy duty grinding and high precision.

- The operating voltage is 110 VDC.
- Can be designed for other operating voltages.
- EM Controller sold separately.

Product Code : EG

All dimensions are in mm.

PART NO	TOP PLATE		POLE PITCH	HEIGHT
	W	L		H
3060	300	600	14 (5+0.5+5+0.5+3)	75
3075		750		
3090		900		
30100		1000		
30120		1200		
30150		1500		
4060	400	600		80
4090		900		
40100		1000		
40120		1200		
5075	500	750		
50100		1000		
50150		1500		
50200		2000		
6075	600	750		
60100		1000		

Due to continuous upgradation in design there could be changes in specification. Other sizes on request. Before ordering, contact Lifton Magnets or your nearest dealer to confirm the suitability of this model for your application.

